

*In re Application: Vick
Serial No. 10/767,579
Filed January 29, 2004
Amendment and Response
Page 2 of 8*

AMENDMENTS TO CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application.

Listing of Claims

Claims 1-34 (Cancelled)

35. (Previously Presented) A device for tightening a strap around freight, comprising:

a. a body capable of being rotated and comprising:

i. a means for holding a first end of a strap; and

ii. a first head positioned at a first end of the body for receiving a

torsion arm; and

b. a clamp coupled to the body for holding a second end of the strap and

comprising:

i. at least two clamp arms, wherein at least one arm is rotatably

coupled to the clamp; and

ii. a cam rotatably coupled to the clamp for securing the at least two

clamp arms at a second end.

36. (Original) The device of claim 35, wherein the means for holding a strap comprises a slot.

37. (Cancelled)

38. (Currently Amended) The device of claim ~~37~~ 35, further comprising a locking arm coupled to the cam for attaching the cam to the clamp arm.

39-40. (Cancelled)

41. (Previously Presented) The device of claim 35, wherein the torsion arm is capable of rotating the body.

42. (Previously Presented) The device of claim 35, wherein the torsion arm is adapted to connect to the first head.

*In re Application: Vick
Serial No. 10/767,579
Filed January 29, 2004
Amendment and Response
Page 3 of 8*

43. (Previously Presented) The device of claim 35, wherein the torsion arm is capable of being removed from the first head.

44. (Previously Presented) The device of claim 35, wherein the torsion arm comprises at least one of the following: a wrench, a ratchet, a bar stock, or integrated portion of the body.

45 - 54. (Withdrawn)

55. (New) A device for tightening a strap around freight, comprising:

- a. a body capable of being rotated and comprising:
 - i. a means for holding a first end of a strap; and
 - ii. a first head positioned at a first end of the body for receiving a torsion arm; and
- b. a clamp coupled to the body for holding a second end of the strap and comprising:
 - i. at least two clamp arms, wherein at least one arm is rotatably coupled to the clamp; and
 - ii. a cam rotatably coupled to the clamp for securing the at least two clamp arms at a second end; and
 - iii. a locking arm coupled to the cam for attaching the cam to the clamp arm.

56. (New) The device of claim 55, wherein the means for holding a strap comprises a slot.

57. (New) The device of claim 55, wherein the torsion arm is capable of rotating the body.

58. (New) The device of claim 55, wherein the torsion arm is adapted to connect to the first head.

59. (New) The device of claim 55, wherein the torsion arm is capable of being removed from the first head.

*In re Application: Vick
Serial No. 10/767,579
Filed January 29, 2004
Amendment and Response
Page 4 of 8*

60. (New) The device of claim 55, wherein the torsion arm comprises at least one of the following: a wrench, a ratchet, a bar stock, or integrated portion of the body.